

ROMAN BLIND



SPECIFICATION

ON MEASURING

Roman blinds have a minimum stack height (this is the height the blind takes up when fully open) of approx. 20cm at the smallest available size. This can vary on the chosen blind and lining fabric

For an accurate stack measurement for your sizes, please contact our customer service team for more information.

Please refer to our Roman measuring guide for a comprehensive guide.

ON FITTING

The sidewinder end comes with a chain cover. Please do not attempt to remove this cover.

When lifting to fit, please ensure you peel the back of the fabric off the headrail, using the Velcro and lift the blind in place using the headrail. This will avoid creasing the fabric face when installed.

GENERAL OVERVIEW

Gear Ratio: 1:4

Finish: Stacked with a slight waterfall finish

Joins: No joins <1200mm | 3 Panels for 1201-2600mm (20/60/20 layout)

Fabric Rod Pockets: Ivory fabric pockets

Rod/Fold Count: Varies by drop (e.g., 2 folds <600mm, up to 4 folds at 2500mm)

Cords: Based on width (e.g., 2 cords up to 900mm, up to 5 at 2500mm)

Headrail Composition: Powder coated Aluminium

Headrail: 43mm depth (including fabric) X 35mm height

Bracket: Universal Top/Face Fix

Bracket Size: 30mm depth x 30mm height

Bottom Bar: 25mm PVC oval bar, sealed in 40mm hem

Side Hems: 20mm | **Bottom Hem:** 40mm

Thread: Colour-matched to fabric

Back Blind Cord: Ivory

Child Safety Cord Clip: Transparent Plastic

Child Safety Max Weight Load: 6kg

Lining Options:

- Standard: Polycotton, White or Cream, 70% polyester / 30% cotton
- Optional: Thermal Lining, Cream, Polyester base with acrylic coating.
- Optional: Blackout, White, Polyester base with acrylic coating.
- Optional: Bonded Interlining, Cream, 70% Polyester 30% Cotton with polyester fleece backing.
- Manufacturing Tolerance: ±5mm