

247 Blinds – Twist&Fit Unlined Voile & Sheers Roman Blind – Specification

Designed by 247 as a drill-free, screw-free solution for fitting Roman blinds.

A classic blind style, Roman blinds are a firm favourite due to their numerous textures, soft fabric and designs available, and with Twist&Fit, fitting just became even easier!

These Roman blinds feature semi-translucent fabrics known as ‘sheer’ or ‘voile’. These fabrics feature a looser weave compared to standard fabrics which allow the light to filter through. These fabrics will arrive unlined to enhance the finished look this fabric achieves.

These blinds arrive unlined, to enhance the finished look this fabric achieves.

Fabric can be easily removed from the headrail for easy access for cleaning the window!

Brackets are not required, and you can fit these blinds in a matter of seconds.

Available under the “recess” fitting option only under the relevant products.

Twist&Fit Roman blinds are supplied with a sidewinder control. The operation is through a chrome beaded chain used to raise and lower.

Blind can be easily removed from the window recess for easy access for cleaning the window!



On Measuring

Roman blinds have a minimum stack height (this is the height the blind takes up when fully open) of 20cm at the smallest size of 40cm width & drop.

This size can vary on the chosen blind fabric.

For an accurate stack measurement for your sizes, please contact our customer service team for more information.

Please refer to our Twist&Fit Roman Blind measuring guide for a comprehensive guide

On Fitting

Sidewinder End comes with a chain cover. Please do not attempt to remove this cover.

Twist&Fit Romans do not require brackets to fit.

When lifting to fit, please ensure you peel the fabric back off the headrail and lift the blind using the headrail. This will avoid creasing the face fabric when installed.

Please ensure you regularly adjust the tension as, due to natural temperature variances, the tension may slack a little.

Components, Linings & Care

Headrail & Twist&Fit Fittings

The headrail is white painted over metal (40mm projection, 40mm height).

Twist&Fit unit is made from POM & PEM materials. This provides a durable, moisture-resistant component.

Raise Rods & Ribbons

Voile Roman blinds require raise rods stitched into the back of the roman. For Voile roman blinds, small ribbons are strategically placed for the cords to raise the fabric. This differs with standard Roman blinds where bars and tapes are used.

There is no "set" placement for these as this can vary from fabric to fabric.

Please be aware of this if buying different fabrics for similar windows in the same room.

Linings

Your new voile Roman blinds come unlined. The semi-transparent sheer fabric will give you a light and airy finish.

Joins

Please note that Roman blinds with a width greater than 120cm MAY have 2 vertical seams due to the fabric width/design.

The reason for having 2 seams is to keep the blind symmetrical: 1 central panel with 2 matched panels either side.

Fabric

All fabric is applied to the headrail using a Velcro heading.

The headrail is white painted over metal (40mm projection, 40mm height).

Fabric is supplied +1cm larger than the headrail for Twist&Fit to cover components.

Overlocked edges to ensure a durable finish

Due to the softened fabric, fabric creasing may be visible out of the box.

Though we pack as carefully as possible to avoid this, please be aware these should naturally “drop out” over 3-7 days.

Allow up to two weeks training for heavier fabrics, such as velvets, for the best result.

Extra's

All items are cut to size and will be accurate with working tolerances and variances of +/- 5mm if under 160cm drop, or +/-10mm if over 160cm drop.

All our blinds are manufactured and supplied to be compliant with child safety regulations.

As part of this compliance, all control cords and chains will be made to a maximum of 1 metre. If you need to discuss this, please contact us.